

Our associates will ensure the tool works properly before you leave the store. If you experience issues with the tool while completing your project, simply bring it back to the Tool Rental Center to get a replacement. If you purchase Damage Protection at the time of your rental, you are not responsible for repair costs for tools that break due to normal use.



**Melcher Manufacturing
Composite Ramp Specifications**



LIGHT DUTY SINGLE RAMPS					
Model	Length (FT)	Width (IN)*	Capacity (LBS)	Weight (LBS)	Working Height Range (IN)
726	7	26	1500	50	12-25
7526	7 ½	26	1500	55	14-27
826	8	26	1500	60	14-30
1026	10	26	1500	84	16-38
1029	10	29	1500	95	16-38
1032	10	32	1500	108	16-38
1226	12	26	1500	98	18-46
1229	12	29	1500	110	18-46
1426	14	26	1500	116	22-54
1626	16	26	1500	145	24-60

*Subtract 2" for usable width.
 Maximum load pressure of 200 pounds per square inch (psi).
 Ramp must be pinned while in use.
 Not to be used with pallet jacks or forklifts. Not sold as dock boards.

Features:

- 1" safety curb height.
- Non-skid walking surface provides safe, secure footing in wet and dry weather.
- Securing pin with in-ramp storage.
- Optional easy lift straps.
- Optional securing chains can be added for an additional cost.
- Easy roll transitions on/off ramp.
- Available for purchase with either an open or fully enclosed underbody carrier.