

Our associates will ensure the tool works properly before you leave the store. If you experience issues with the tool while completing your project, simply bring it back to the Tool Rental Center to get a replacement. If you purchase Damage Protection at the time of your rental, you are not responsible for repair costs for tools that break due to normal use.



TLR33 TRAILER



TILT BED DESIGN. The tilt bed design helps make it more convenient to load and unload without ramps.



WHEEL CHOCK LOCATION. There are seven holes available to position the chocks as needed for different sized machines.



VERSATILITY. The TLR33 trailer comes with several different tie-down system options to meet your transporting needs.



TRANSPORT. Bolted on safety chains helps give peace of mind when traveling on the road with equipment loaded on the trailer. Plus a common 2" (5.1 cm) ball hitch to accommodate most towing vehicles.



SURFACE TRACTION A replaceable "expanded metal" floor, this material is bolted to the trailer deck and provides traction for loading and unloading of equipment.



OPTIONAL BRAKES. The TLR33 trailer comes with the option to include electric brakes for better towing control.



VERMEER.COM



EQUIPPED TO
DO MORE.

TLR33 TRAILER

GENERAL WEIGHTS AND DIMENSIONS

Overall Length: 141" (358.1 cm)

Width: 71.5" (181.6 cm)

Tongue height: 19.5" (19.5 cm)

Floor bed width: 50" (127 cm)

Floor bed height: 12" (30.5 cm)

Floor bed length: 96" (243.8 cm)

Rear width between fenders: 52" (132.1 cm)

Maximum gross vehicle weight rating: 2950 lb (1338.1 kg)

Max gross axle weight rating: 3160 lb (1433.4 kg)

Weight: 771 lb (349.7 kg)

Tongue weight: 50 lb (22.7 kg)

Maximum cargo weight: 2130 lb (965 kg)

UNDERCARRIAGE

Brakes: Optional (electric)

Tires: ST 185/ 80D13(D)

Number of axles 1

Tail lights with plate holder: Yes

Fenders: Yes

Rims: 13" x 4.5" (33 cm x 11.4 cm) custom spoke 5-bolt

Safety chain size: Dual zinc-plated with hooks

Tongue jack: 2,000 lb (907.2 kg) weld on foot

Tie down kits (optional): Chains, hooks, binder or wheel chocks;
Binderless tie down

Hitch type: 2" (5.1 cm) ball