

# Deck Frame Coating

Rubberized Protective Waterproofing Membrane

**NEW  
PRODUCT**

## Extend the Life of Your Deck Frame!

FastenMaster Deck Frame Coating extends the life of your deck substructure by creating a protective moisture barrier that deters wood rot and decay on deck joists, beams, ledgers, stair stringers and posts.



### **Extends Life Of The Deck Frame**

Creates a lasting moisture barrier protection



### **Fast And Clean Application**

No mess coverage with less jobsite waste



### **Dries in as little as 20 minutes \*\***

Sets fast for deck board installation



### **Coats Hard-To-Reach Places**

Use in corners tape cannot reach



**Deck Joists**



**Deck Carrying Beams**



**Stair Stringers**



Can be applied using a  
standard bristle paint brush  
or a heavy nap roller.

**FastenMaster.**  
**Deck Frame Coating**



# **FastenMaster.** **Deck Frame Coating**

## APPLICATION:

FastenMaster's Deck Frame Coating can be applied using a standard bristle paint brush or a heavy duty, 3/8" nap roller. It is recommended to apply a generous and consistent single layer of coating.

- Apply in temperatures above 40 °F / 4 °C. Freeze/thaw stable when cured.
- Product is in a liquid state, protect from freezing.  
If product was frozen, allow 12 hours of thaw time before use.
- Fast dry formula sets in as little as 20 minutes.\*\*
- Full cure in 24 hours @ 70°F/21°C and 50% humidity.\*\*
- Do not apply to dirty/contaminated or wet surfaces.
- Coating remains slightly tacky when cured.

## CLEAN UP:

Clean skin or building materials using soap & warm water. Mineral oil or Baby Oil can be used. It is recommended to review the decking manufacturer's warranty before using cleaners.

## CAUTION:

Keep out of reach of children & pets. Wear gloves, eye protection and avoid contact with clothing. If in eyes, flush with water for several minutes. Get medical attention if irritation persists. If swallowed call a poison center or doctor for advice. Low VOC waterproofing sealer contains <100g/L VOC.

### Product Listings

Description	Coverage	SKU
1 gallon bucket	450 LF	FMDFC-1GAL

For a full written warranty, additional engineering data and technical support visit [FastenMaster.com](http://FastenMaster.com).

\*Approximate coverage per gallon at 20mil or .5mm dry film thickness

\*\*High temperature and / or high humidity may extend set time.

**For use on Deck Joists, Stair Stringers, Deck Carrying Beams, Deck Posts and More!**



**See How  
Quick And Easy  
It Is To Apply**

